

Draco Mini

The Draco LED is a 144mm diameter downlight which uses a Cree XP-E LED Array. The heatsink is constructed from die-cast aluminium complete with aluminium bezel and polished reflector. The downlight is available in outputs from 1300lm to 1700lm and as standard is rated IP20.


- CREE LED Engine
- Cast Aluminium
- Instant on no flicker
- Environmentally Friendly No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span



General

Dimensions Ø144 x 66mm Cutout Ø125mm Installation Ceiling Tile Plasterboard **Beam Angle** 30° / 45° / 75° AC220-240V Voltage CE, ROHS Certification Warranty 5 Years





Performance

Compliance

Colour Rendering Ra>80/90 Longevity 50,000 hours **System Power** 15 W

20 W

Exit Lumens 1,440 lm @4000K 1,600 lm @4000K

86 lm/W

Efficiency 85 lm/W

Building Regulations

ETL (Energy Technology List) ECA (Enhanced Capital Allowance)

SKA Rating

Available options

Wattage	15W - 1300 lm, 20W - 1700 lm
Colour	White, Special RAL Colour
Colour Temperature	3000K, 4000K, 5000K
Beam Angle	30°, 45°, 75°
Dimming	Fixed Output, 1-10v Dimming, DALI Dimmable, Mains Dimming, Swith Dimming
Emergency	Not required, 3 Hour Facility, 3 Hour Self Test, 3 Hour Central Test, Central Battery System

Product Code: DRC-M