

LED UK

HAZX Delta

The HAZX Delta luminaire is a linear explosion-proof LED which can be used in Zone 2 (Gas) and Zone 21 & 22 (Dust). The luminaire is based on a dual chamber structure with the LED light sources and LED driver being housed separately for heat dissipation. The HAZX Delta is finished with an anodic coating with an impact resistant polycarbonate lens. All fixings are stainless steel.



- Zone 2 (Gas) & Zone 21 & 22 (Dust)
- Atex Certified
- CREE LED
- Excellent EMC compatibility
- Dual chamber design for integral gear and LEDs
- Over 50,000 hours life span

General

Dimensions	9W = 211 x 70 x 124 mm
	18W = 411 x 70 x 124 mm
	36W = 611 x 70 x 124 mm
Weight	9W = 1.1 kg
	18W = 2.0 kg
	36W = 2.8 kg
Voltage	90-260Vac 50/60Hz
Classification	ExnAII T6 Gc/ExtIIIBT85°C Db
Zone	Zone 2 (Gas)
	Zone 21 & 22 (Dust)
Warranty	5 Years

Performance

IP rating	IP65
Colour Rendering	Ra>80
Longevity	50,000 hours
System Power	9.5 W
	18.7 W
	37.2 W
Exit Lumens	958 lm
	1,891 lm
	3,788 lm
Efficiency	100.8 l/cW
	101.1 l/cW
	101.8 l/cW
Compliance	ATEX Certified

LED UK

HAZX Delta

Available options

Wattage	9W - 900 lm, 18W - 1,800 lm, 36W - 3,600 lm
Colour Temperature	3000K, 5000K
Installation Type	Surface Fixed, Surface Adjustable, Pendant (Rod), Pendant (Chain), Bent Pole, Flange, Fence
Lens Cover	Nickel Plated Steel, Stainless Steel
Emergency (Excludes 36W Version)	Not Required, 3 Hour Emergency Facility

Product Code: HAZX-DTA