

Impact 1500mm

The IP66 1500mm Impact LED is a vapour-proof luminaire with a IK10 Impact Rating which is available in 50W, 60W and 80W variations. The luminaire body is constructed from GRP and ABS which houses the singular LED board. The lens is part frosted to reduce glare from all viewing angles. The Impact is available with a variety of Emergency options including Central Battery System.

- IK10 Impact Rating
- 5 year warranty
- 50,000 hours
- Mercury free, No UV or IR
- Instant start and flicker free



General

| | |
|---------------|--|
| Dimensions | 1500 x 93 x 69mm |
| Weight | 2.6kg |
| Installation | Ceiling Surface Ceiling Suspended Wall Surface |
| Voltage | 200-240Vac 50/60Hz |
| Certification | SAA, TUV, CE, GS, CB, ERP |
| Warranty | 5 Years |

Performance

| | |
|-----------------------|--|
| IP Rating | IP66 |
| Operating Temperature | -15 - 45°C |
| Colour Rendering | Ra>80-85 |
| Longevity | 50,000 hours |
| System Power | 51.5 W 62.3 W 80.0 W |
| Luminous | 50 W - 5800Lm 60 W - 6000Lm 80 W - 8000Lm |
| Efficiency | 100.0 lm/cW 100.0 lm/cW 100.0 lm/cW |
| Compliance | Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating |

Impact 1500mm

Available options

| | |
|--------------------|--|
| Wattage | 50W (1500mm Module), 60W (1500mm Module), 80W (1500mm Module) |
| Colour Temperature | 3000K, 4000K, 6000K |
| Mounting Option | Surface Adjustable, Surface Fixed, Suspended |
| Microwave Sensor | Not Required, Microwave Sensor |
| Cable Entry | Side Entries (IP68 connectors), Rear Entry |
| Dimming | Fixed Output, 1-10V Dimming, DALI Dimming, Switch Dimming |
| Emergency | Not required, 3 Hour Facility, 3 Hour Self Test, 3 Hour Central Test, 3 Hour Central Battery |

Product Code: IMP