

LED UK

Imperial Flood

Imperial flood lighting range is available in various beam angles providing either a symmetrical or asymmetrical light output. The Philips LED array provides 150 Lm/W with a CRI of Ra80. The flood light range is powered by Meanwell LED Drivers providing either a fixed output or dimmable solution.

- Philips SMD5050 LED Array
- IP65 rated
- Aluminium body
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 80,000 hours life span
- 5 Year warranty



General

Dimensions	516 x 388 x 109mm
Weight	11.9 kg
Installation	Bracket mounted
Voltage	100-277Vac 50/60Hz
Certification	CE, ROHS
Warranty	5 Years



Performance

IP Rating	IP65
Operating Temperature	-40°C - 45°C
Colour Rendering	Ra>80
Longevity	50,000 hours
System Power	400 W
Initial Lumens	60,000 lm
Efficiency	150 lm/cW
Beam Angle	60°
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating

LED UK

Imperial Flood

Available options

Wattage	400W
Colour Temperature	3000K, 4000K, 5000K, 6000K
Beam Angle	60°
Dimming	Fixed Output, 1-10V Dimming, DALI Dimming

Product Code: IMF