

# LED UK

## Levo Square Mini

Levo Square Mini Trimless Downlight is a 71 x 71mm plaster in luminaire providing a low glare and functional light output along with a seamless architectural installation. The fitting is constructed from die-cast aluminium and is complete with a choice of white, gold or black inner baffle. The fitting is fitted with a Philips LED providing a luminaire luminous flux of 700 lumens. The luminaire may be tilted to a maximum of 30 degrees.

- Philips LED
- Cast Aluminium
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span
- Available in a range of beam angles

### General

|               |                 |
|---------------|-----------------|
| Dimensions    | 71 x 71 x 103mm |
| Cutout        | 72 x 72mm       |
| Weight        | 0.4kg           |
| Beam Angle    | 15/24/30/36     |
| Installation  | Plasterboard    |
| Voltage       | 220-240Vac      |
| Certification | CE, ROHS        |
| Warranty      | 5 Years         |
| IP Rating     | IP20            |

### Performance

|                  |  |
|------------------|--|
| Colour Rendering | Ra>82  |
| Longevity        | 50,000 hours   |
| System Power     | 10.0 W   |
| Exit Lumens      | 700 lm   |
| Efficiency       | 70.0 lm/cW   |
| Compliance       | Building Regulations<br>ETL (Energy Technology List)<br>ECA (Enhanced Capital Allowance)<br>SKA Rating |

### Available options

|                    |  |
|--------------------|--|
| Wattage            | 10W - 700 lm   |
| Colour             | Gold, Black, White   |
| Colour Temperature | 2700K, 3000K, 4000K  |
| Beam Angle         | 15, 24, 30, 36   |
| Lens               | Clear  |
| Dimming            | Fixed Output, 1-10V Dimming , DALI Dimmable, Mains Dimming, Switch Dimming                   |
| Emergency          | Not Required, 3 Hour Facility, 3 Hour Self Test, 3 Hour Central Test, Central Battery System |

Product Code: LVS-M

