

LED UK

Optus

Low profile emergency LED fitting suitable for varied application types and inclusive of all emergency gear and batteries. A choice of optics allow for either Open Area or Corridor light distribution. The body is fitted with a Bi-Colour LED indicating the health of the fitting and battery.

- Architectural appearance
- 3W with up to 207lm output
- Instant on - no flicker
- Over 35,000 hours life span
- Remote emergency 3 Hour control gear
- Choice of Optics



General

Dimensions	LED Head = 50mm Diameter Driver = 26.5mm (H) x 150mm (L) Battery = Ø29 x 170mm
Cutout	LED Head = Ø43mm
Weight	1.8kg
Installation	Recessed 24mm T-Grid Recessed Burgess Recessed Plasterboard
Voltage	200-240Vac 50/60Hz
Certification	CE, ROHS
Warranty	5 Years

Emergency

Colour Rendering	Ra>80
Longevity	35,000 hours
System Power	3 W
Exit Lumens	Up to 207 lm
Compliance	Building Regulations
Optics	Open Area - 207 Lumens Corridor - 197 Lumens

Available options

Wattage	3 Watt
Emergency	3 Hour Facility, 3 Hour Self Test, 3 Hour Central Test DALI
Body Finish	White, Silver, Black
Light Distribution	Corridor - 197 Lumens, Open Area - 207 Lumens

Product Code: OPT