


Proteus

The Proteus LED is a linear luminaire which is available in lengths of 600mm, 1200mm & 1500mm. The luminaire body and lens are constructed from polycarbonate which houses the LED board giving a beam angle of 120°. The polycarbonate lens is retained via stainless steel clips to ensure an IP69 rated seal. The luminaire has an impact rating of IK10 & the operating temperature for standard fittings is between -20°C to +40°C.

- IP69 rated
- 600/1200/1500mm modules
- 5 year warranty
- 50,000 hours
- Mercury free, No UV or IR
- Instant start and flicker free
- Rated IK10



General

Dimensions	20W - 600mm Length x 75mm Diam 36W - 1200mm Length x 75mm Diam 45W - 1500mm Length x 75mm Diam
Installation	Ceiling Surface Ceiling Suspended
Voltage	100-240Vac 50/60Hz
Certification	SAA, CE, UL, DLC, TUV-GS, ROHS
Warranty	5 Years

Performance

Colour Rendering	Ra>80
Longevity	50,000 hours
System Power	20 W 36 W 45 W
Exit Lumens	2200-2600 lm 4000-4700 lm 5000-5900 lm
Efficiency	110 - 130 lm/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating
IK Rating	IK10

Available options

Wattage	20W (600mm Module), 36W (1200mm Module), 45W (1500mm Module)
Colour Temperature	3000K, 4000K, 5000K
Mounting Option	Surface, Suspended
Dimming	Fixed Output, 1-10v Dimming, DALI Dimming, Switch Dimming
Emergency	Not required, 3 Hour Facility, 3 Hour Self Test, 3 Hour Central Test, Central Battery System

Product Code: PRS