


LED UK

RI Series - 6.2 mm Pixel Pitch

6.2 mm Pixel Pitch, Indoor High Resolution LED Curtain

- Slim and lightweight design
- Modular module design allows for quick and easy maintenance
- Build in curve structure
- High transparency
- High refresh rate



Item	RI-SC-6.2
Pixel Pitch	6.2mm
LED Configuration	SMD3528
Pixel Density	25600/m ²
Unit Resolution	40x20
Unit Weight	9.5kg
Module Resolution	28x14
Scan Mode	1/10
Brightness(cd/sqm)	?3500/?6000
Driver IC	MBI5024/MBI5041/MBI5151
Refresh Frequency	?800Hz
	?1200Hz
	?2000H
Max Power Consumption(W/pc)	200
Avg Power Consumption(W/pc)	70
Gray Scale	?12bit
	?14bit
	?16bit
Transparency	13%
Module Size(mm)	250(W)x125(H)
Unit Size(mm)	500(W)x1000(H)x71(D)
View Angle	H140°/V90°
Curved Angle	±30°/no curved
IP Level(front/rear)	IP65/IP54
control system	NOVA/DBSTAR/LINSN
Working Temperature	-30°C - +50°C
Operating Humidity	10-90% RH

LEDUK

RI Series - 6.2 mm Pixel Pitch

Product Code: RI-SC-6.2