

Ring

Ring suspended is rigid circular linear luminaire range constructed from extruded aluminium with a polycarbonate diffuser giving an efficient and low glare output, this profile can also be specified with an optional uplight facility. Ring fittings are available in a number of sizes ranging from 450mm to 7000mm in diameter. Other sizes and custom lumen package are available on request, to discuss your requirements please contact us at sales@led.uk.



- Aluminium profile
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span
- Direct only or Direct/Indirect (up/down) light distribution.

General

Dimensions (H x Dia.)	60 x 450 60 x 660 60 x 900 60 x 1060 60 x 1200 60 x 1560 60 x 1860 60 x 2060 60 x 2460 60 x 3060 60 x 4060 60 x 5060 60 x 6060 60 x 7060
Installation	Suspended Surface Recessed
Input Voltage	100-240Vac 50/60Hz
Certification	CE, ROHS
Warranty	5 Years

Available options

Mounting Option	Suspended, Surface, Recessed
Size	450mm, 600mm, 900mm, 1060mm, 1200mm, 1560mm, 1860mm, 2060mm, 2460mm, 3060mm, 4060mm, 5060mm, 6060mm, 7060mm
Uplight	Not Required, Low Output, Standard Output
Profile Colour	White, Black, Special RAL Colour
Colour Temperature	2700K, 3000K, 4000K, 6500K
Dimming	Fixed Output, 1-10V Dimming, DALI Dimming
Emergency	Not Required, 3 Hours Facility (Remote), 3 Hours Self Test (Remote), 3 Hours Central Test (Remote)

Product Code: RNG