
Sirius IP Max

The Sirius IP Max LED is a 230mm diameter downlight which uses a CREE LED engine. The heatsink is constructed from die-cast aluminium complete with aluminium bezel and reflector. The heatsink features adjustable fold-out arms which allows the Sirius IP Max to be installed with ease. The downlight is available in outputs from 1500lm to 3300lm. The luminaire is supplied with a frosted diffuser giving the downlight a IP54 rating.




- CREE LED Engine
- IP54 Rating
- Cast Aluminium
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span

General



Dimensions	Ø230 x 99mm
Cutout	Ø210mm
Weight	1.9kg
Beam Angle	90°
Installation	Ceiling Tile Plasterboard
Voltage	220-240Vac
Certification	CE, ROHS
Warranty	5 Years
IP Rating	IP54





Performance

Colour Rendering	Ra>82
Longevity	50,000 hours
System Power	20.6 W 25.4 W 30.8 W 36.0 W 40.2 W
Exit Lumens	1,901 lm 2,345 lm 2,857 lm 3,330 lm 3,702 lm
Efficiency	92.3 ll/cW 92.3 ll/cW 92.8 ll/cW 92.5 ll/cW 92.1 ll/cW

Sirius IP Max

Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Carbon Allowance) SKA Rating

Available options

Wattage	20W , 25W , 30W , 35W , 40W
Colour	White, Special RAL Colour
Colour Temperature	3000K, 4000K, 6000K
Lens	Frosted Lens
Dimming	Fixed Output, 1-10V Dimmable, DALI Dimming, Mains Dimming, Switch Dimming
Emergency	Not required, 3 Hour Facility

Product Code: SRS-X