

LED UK

Splice

The Splice is a surface mounted 20mm wide continuous luminaire available in 500mm sections. The Splice has a minimalist appearance in the ceiling which makes it ideal for architectural spaces. The fitting is made from extruded aluminium with a polycarbonate diffuser to achieve a highly efficient linear profile.



- Aluminium profile
- Frosted polycarbonate diffuser
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span

General

Dimensions	20 x 19.7 x 500mm
	20 x 19.7 x 1000mm
	20 x 19.7 x 1500mm
	20 x 19.7 x 2000mm
Weight	0.4 kg
	0.8 kg
	1.2 kg
	1.6 kg
Beam Angle	120°
Installation	Surface
Voltage	220-240Vac
Certification	CE, ROHS
Warranty	5 Years

Performance

Colour Rendering	Ra>80
Longevity	50,000 hours
System Power	3.1 W
	6.1 W
	9.1 W
	12.2 W
Exit Lumens	298 lm
	595 lm
	893 lm
	1,190 lm
Efficiency	97.5 ll/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating

Available options

Length	500mm, 1000mm, 1500mm, 2000mm
Module	Standalone, Start, Middle, End
Profile Colour	Aluminium
Colour Temperature	3000K, 4000K, 6000K
Wattage	3.1W/m, 5.1W/m, 9.1W/m, 12.2W/m, 14.4W/m
Dimming	Fixed Output, DALI Dimming

Product Code: SLI