

# LED UK

## Union Max Floodlight

The floodlight is constructed from high grade cast aluminium finished with a zinc coating for interior and exterior use. The highly efficient Cree LED light source creates exit lumen packages ranging from 26,000 to 91,000lm

- Cree LED chips
- 50,000hours
- 3000K, 4000K & 6000K
- DALI / 0-10Vdc dimming
- Photocell sensor system
- Built-in surge protection
- Built-in thermal protection
- Maintenance free
- Mercury free, No UV or IR
- Instant start and flicker free
- Patent multi-function design
- Up to 10 year warranty



### General

Dimensions	468 x 388 x 367mm
Weight	15.0 kg
Certification	SAA, TUV, CE, GS, CB, ERP
Warranty	Up to 10 Years



### Performance

Operating Temperature	-40°C - 60°C
Colour Rendering	Ra>80
Longevity	50,000 hours
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating

# LED UK

## Union Max Floodlight

---

### Available options

Wattage	300W, 400W, 500W, 600W, 700W
Colour Temperature	Warm White (3000K), Neutral White (4000K), Cool White (6000K)
Beam Angle	40°, 60°, 120°, 140°
IP Rating	IP67
Mounting Option	Pendent, Pole, Bracket
Dimming	Fixed Output, 1-10V Dimmable, DALI Dimmable
Photocell	Not Required, Microwave Sensor, Photocell
Input	110-480Vac
Light Distribution	No Beam Control, Horizontal Hood, Lens Guard, Horizontal Hood + Lens Guard

Product Code: UNI